



TYPICAL CROSS SECTION WITHIN ROAD RESERVE

TYPICAL CROSS SECTION UNDER PAVEMENT

NOTES:

1. COMPACTION TESTS TO BE UNDERTAKEN BY A NATA REGISTERED TESTER FOR SEWER AND DRAINAGE TRENCH BACKFILL, AND THE RESULTS FORWARDED TO WYNDHAM CITY COUNCIL'S CONSTRUCTION SUPERVISOR.
2. REFER TO WYNDHAM CITY COUNCIL'S GENERAL SPECIFICATION, SECTION 701, FOR DETAILS ON MATERIALS AND COMPACTION CRITERIA.
3. TRENCH WIDTH = PIPE OUTSIDE DIAMETER + 300mm.
4. IF TRENCH IS IN/THROUGH EXISTING PAVEMENT, REINSTATEMENT WIDTH OF PAVEMENT IS: WEARING COURSE = TRENCH WIDTH + 500mm EACH SIDE OF TRENCH.

Rev	Amendments	Approved	Date
B	Minor Drafting Standards		16-05-07



CULVERT TRENCH BACKFILLING SPECIFICATIONS	
Engineering Services Approval No.: ES001	Date: 21/05/09

Cad File : SD6-10A.DWG
Drawn Date : 02/02/09
Revision : B
Drawing No. SD6-10A

GENERAL NOTES:

- DRAWINGS ARE NOT TO SCALE.
- ALL MEASUREMENTS ARE IN MILLIMETERS UNLESS OTHERWISE STATED.
- FOR UP TO DATE DRAWINGS PLEASE CHECK WYNDHAM CITY COUNCIL WEB SITE.
- ALL STANDARD DRAWINGS TO BE USED IN CONJUNCTION WITH SD1-1 (STANDARD DRAWINGS CONDITIONS OF USE).